

# RPZ-OPTO SL DATA SHEET



## RPZ-OPTO INDUSTRIAL PALLETIZING

THE RPZ-OPTO palletizing solution was born out of a need for manufacturers that are challenged with limited space. Configurable pallet handling modules eliminate the need for frequent operator intervention, reducing labor costs and increasing productivity rates.

### **KEY FEATURES**

- Modular Design
- Flexible Tooling Options
- Easy-To-Use Dashboard
- Data Logging
- Integrated Tier Sheet Handling
- Stretch Wrapper
   Integration Available

# CONTACT

sales@iriscs.com 630-634-7700 irisfactoryautomation.com

# **TECHNICAL SPECIFICATIONS**

Power Requirement	480 VAC
Empty Pallet Queue	15 Pallets*
Air Requirement	90 PSI Minimum
Stretch Wrap Integration	Available Upon Request
Recipe Building	Full Container Height
Maximum Payload	180kg, less EoAT
<b>Maximum Pick Rate</b>	Up to 12 Cycles per Minute
Maximum Pallet Height	Full Container Height
Pallet Formats	GMA, CHEP, PECO
Pallet Conveyance	MDR, Drag Chain
Robot Platform	Fanuc or Kawasaki

\*dependent on OPTO Model

